スプリングプランジャ


ロングストロークタイプ

SPRING PLUNGER

SPLL (軽荷重タイプ) SPLH (重荷重タイプ)









〈材 質〉ノーズ SK95 ネジ部 SCM435 〈硬 さ〉HRC36~40 〈表面処理〉黒色クロメート 亜鉛メッキ

Catalog No.	M	ストローク S	D	L	Lı	MxP	荷重 N(kgf)	
							初期	最終
	12	10	5.5	43		M12xP1.75	3.9 (0.4)	19.6 (2.0)
		10					12.7 (1.3)	
SPLL	16	15	8.0	60	35	M16xP2.0	9.8 (1.0)	39.2 (4.0)
		20					12.7 (1.3)	
		30		125			17.6 (1.8)	
	24	15	10.0	60	45	M24xP3.0	19.6 (2.0)	98.0 (10.0)

Catalog No.	M	ストローク S	D	L	Lı	MxP	荷重 N(kgf)	
							初期	最終
	12	10	5.5	43		M12xP1.75	6.8 (0.7)	39.2 (4.0)
	10 15 20		60			26.4 (2.7)		
SPLH		15	8.0	60	35	M16xP2.0	14.7 (1.5)	78.4 (8.0)
		20	0.0	85			16.6 (1.7)	
		30		125			19.6 (2.0)	
	24	15	10.0	60	45	M24xP3.0	39.2 (4.0)	196.1 (20.0)



Catalog No. S **SPLH** 16 20



プランジャ用レンチP.29参照。


プランジャ用レンチ

WRENCH FOR PLUNGER

● SPLL/SPLH/SPXL/SPXH/NSPS/NSPL用レンチ

PW





Catalog No.	プランジャ M	н	d	D	L
	5	40	3	6	40
	6	40	3	6	40
	8	45	4	8	45
DW	10	45	4	10	45
PW	12	50	5	12	50
	16	70	8	16	52
	24	80	12	24	62
	30	100	15	30	73



Catalog No. **PW** 12

● PRJM/PRJL用レンチ

PRJR16



Catalog No. PRJR16



Catalog No. PRJR16